

# 716 Derby Promotions



## 80's & Newer Bone Stock Full Size & Bone Stock Minivans

### General:

- This class will be limited to 1980's and newer cars and minivans, no cars considered old iron will be allowed.
- Helmet, seat belt, long sleeves/pant and eye protection must be worn at all times on the track.
- Cars and vans must be stock
- You may have a 12"x12" roof sign that does not strengthen the vehicle in any way.
- Vehicles must be swept clean of debris and glass before coming to event.
- Battery can be left in stock location but you must put a rubber mat over it or spray foam around it, **NOT** excessively. **Do NOT spray foam on anything else.**
- Battery needs to be moved to inside of vehicle. You may lengthen the cables to reach the battery on the floor.
- Judges Decision is Final. All vehicles are subjected to re-inspection at any time

### Build:

- No cross breeding, entire drive must be same make as vehicle (Chevy to Chevy, Ford to Ford and so on) Must have factory engine to vehicle
- Engine must be mounted with stock mounts in stock position.
- No welding of mounts. Must be bolted only.
- No homemade cross members. Cross members must be stock and bolted in not welded.
- Doors may be fastened in 6 spots per door. 3/8" chain, #9 wire or 2" x 2" x 1/4" plates. If #9 wire is used then the wire from the bottom of the doors may go around frame. You may have a four bar floating cage not to exceed 6 inch cage material, cannot go any further back than 6 inches of front doors. Front bar must be in dash area, must be at least 5 inches off floor. You are allowed a floating gas tank protector, but there must be a big enough gap between the protector and the sheet metal to fit my hand in between the two. NO UPRIGHTS, KICKERS, ETC COMING OFF YOUR CAGE/GAS TANK PROTECTORS. You may have a halo as well but can only go from top of floating cage vertically up and over the top of roof and back down to the top of floating cage. Cannot go to floor or frame.
- Trunks must be chained, wired or welded. No more than 6 spots. If welded (2" x 2" x 1/4" plates). If chained or wired they may go around bumper in 2 spots. • Vans must have deck lid/tailgate No welding or adding metal. Trunk lid must be in fastened on stock hinges in

stock location. You can tuck 50% of trunk lid only or remove trunk lid completely. No pre-bending of frame or wedging of trunks. No welding washers for holes.

- Hoods may be chained or wired in 6 spots. You may use 5/16" chain or 2 strands of #9 wire per hole. It must be sheet metal to sheet metal only. No welding washers for holes. Two of your 6 hood tie downs can go through core support holes with spacer or you can well all thread to the side of frame, NO more than 2" of weld down the side of frame. All Thread cannot be any larger than 3/4" in diameter. You are allowed to have header pipes out of the hood. If you choose **NOT** to have pipes you must have a 12" hole in hood in case of fire. Remove hood latch! Hood must be open for inspection.
- Any tires permitted & double tires permitted. No foam filled tires. small valve stem protectors are allowed.
- You may leave stock gas tank in stock location if it is in front of rear tires or you may relocate the fuel tank to rear floor of vehicle, if this is done you must use a fuel cell or boat tank. No stock fuel tanks allowed inside of vehicle.
- Must remove windshields
- NO CREASING ON THE BODY IS ALLOWED!!!
- Stock type springs and shocks. No solid suspension. Screw in type risers are okay, no wire, chains or any weld on rear ends or rear spring pockets. Vans must bounce!!
- You must use factory rear end for the vehicle you are running.
- You may weld spider gears in rearend to make it posi. No gears are allowed, you must use stock axles. You are not allowed to change the gear ratio or use aftermarket axles. Bumpers:
- You may ONLY use an 80 & Newer bumper on car. It must bolt on in the factory location and you may collapse the shocks and weld all the way around the shock and the plate to bumper as well as you can add one - 4"x6"x1/4" plate per frame rail. If car has no shocks, bumper may be welded directly to frame, you can use one - 4"x6"x1/4" plate per frame rail. Ends of bumpers must be open and NO added metal. No replica bumpers (front or back), you are allowed a 4"x4"x1/4" square tubing with ends of bumper open. It cannot be wider than the front tires of vehicle.
- If the vehicle has a wiring harness in front of the core support you may move it behind the core support.
- All body bolts must be factory stock no altering permitted.
- No shortening of frame.
- HANDICAP MINIVANS ARE NOT ALLOWED!
- If there is visual damage on a pre-ran vehicle you may have a total of 2 – 4"x4"x1/4" plates per frame rail. Please call for questions.

**IF IT DOESN'T SAY YOU CAN SPECIFICALLY DO SOMETHING THEN YOU CAN'T!**

**Judge's Decision are Final!**

**Thank you for taking the time to read the rules! Please build to the rules and we look forward to seeing all of you this 2026 season! Let's have some fun and put on a good show for the crowd!**

If you have any questions, please contact:

Jesse Hamm

620-381-4762

Jwhamm@live.com